

## **Material: Carboxylated Nitrile Rubber (XNBR)**

**MAX SPARE Code: XN 75** 

Physical properties  Hardness	Nominal 75-85	Units
Hardness	75-85	
naiuless		Shore A
ASTM D 2240, 23°C		
Tensile strength	> 102	Kg/cm <sup>2</sup>
ASTM D 412, 23°C		
Elongation at break	> 125	%
ASTM D 412, 23°C		
Compression set	< 25	%
ASTM D 395, 100°C, 22 h, 25 %		
Air Ageing		
ASTM D 573, 100°C, 70 h		
Hardness Change	± 10	Points
Tensile Change	<(-20)	%
Elongation Change	<(-30)	%
Fluid Resistance, IRM-901		
ASTM D 471, 100°C, 70 h		
Hardness Change	-10 to+5	Points
Tensile Change	<(-20)	%
Elongation Change	<(-30)	%
Volume Change	0 to +20	%
Fluid Resistance, IRM-903		
ASTM D 471, 100°C, 70 h		
Hardness Change	<(-20)	Points
Tensile Change	<(-50)	%
Elongation Change	<(-50)	%
Volume Change	0 to +25	%
Specific Gravity	$1.20 \pm 0.02$	g/cc
ASTM D 792, 23°C		
Service Temperature	-30 to 100	°C

## Disclaimer